

Thumbscrew
Position selectable
(120deg)

1" 1.4/12.5mm C	1"	2/3"	1/1.8"
FOCAL LENGTH	f=12.5mm		
MAX. DIAMETER (RATIO)	F=1 : 1.4~16		
PICTURE SIZE	9.6x12.8mm	6.6x8.8mm	5.4x7.2mm
ANGLE	VER. ANGLE	42.5°	29.5°
	HOR. ANGLE	55.6°	39.1°
	DIA. ANGLE	67.6°	48.3°
DISTORTION (TV)	-1.58%		
SHOOTING RANGE AT	VER.	243.5mm	165.2mm
MINIMUM FOCUS	HOR.	330.6mm	222.4mm
DISTANCE	DIA.	420.6mm	281.3mm
MINIMUM FOCUS DISTANCE		0.3m	
FLANGE BACK		17.526mm in air	
BACK FOCUS		12.6mm in air	
FILTER SCREW SIZE		M35.5x0.5	
FRONT/REAR EFFECTIVE DIA.		FRONT Φ28.1mm	REAR Φ17.5mm
MOUNT		C-MOUNT	
EXIT PUPIL		-45.9mm	
TEMPERATURE RANGE		-10~+50 °C	
STORAGE TEMPERATURE RANGE		-20~+60 °C	
RESOLUTION CENTER/CORNER		CENTER 120lp/mm	CORNER 80lp/mm
WEIGHT		160 g	

NOTE: Specifications and availability are subject to change without notice
注)本仕様については、予告なしに変更する場合があります。

Kowa

		尺度	1/1	工場番号	HR976SW
2015.7.30	正面図追加	機種名	1" F1.4 f=12.5mm		
2014.12.25	更新	機種番	LM12HC-SW		
2013.4.15	作成年月日				




LM12HC-SW

Working distance: 1m

F-stop: F1.4


Wave length: 1000nm – 1500nm



Working distance: Infinity


F-stop: F1.4

Wave length: 1000nm – 1500nm






LM 1 2 HC - SW






LM12HC-SW


Distortion (Object ∞)

Distortion (Object 1.0m)







Distortion (Object 0.3m)





LM12HC SW

Lateral Color Aberration



Maximum Scale: $\pm 500 \mu\text{m}$

LM12HC-SW (976IR) Transmission

