


Thumbscrew
Position selectable
(120deg)



1" 1.4/25mm C	1"	2/3"	1/1.8"
FOCAL LENGTH	f=25mm		
MAX. DIAMETER (RATIO)	F=1 : 1.4~16		
PICTURE SIZE	9.6x12.8mm	6.6x8.8mm	5.4x7.2mm
ANGLE	VER. ANGLE	22.0°	15.1°
	HOR. ANGLE	29.3°	20.2°
	DIA. ANGLE	36.6°	25.2°
DISTORTION (TV)	-1.0%		
SHOOTING RANGE AT	VER.	119.2mm	81.4mm
MINIMUM FOCUS	HOR.	160.7mm	109.1mm
DISTANCE	DIA.	204.3mm	137.4mm
MINIMUM FOCUS DISTANCE		0.3m	
FLANGE BACK		17.526mm in air	
BACK FOCUS		16.5mm in air	
FILTER SCREW SIZE		M35.5x0.5	
FRONT/REAR EFFECTIVE DIA.		FRONT φ21.0mm	REAR φ19.4mm
MOUNT		C-MOUNT	
EXIT PUPIL		-57.9mm	
TEMPERATURE RANGE		-10~+50 °C	
STORAGE TEMPERATURE RANGE		-20~+60 °C	
RESOLUTION CENTER/CORNER		CENTER 120lp/mm	CORNER 80lp/mm
WEIGHT		135 g	

NOTE: Specifications and availability are subject to change without notice
注)本仕様については、予告なしに変更する場合があります。




		尺度	1/1	工場番号	HR978NCN-3H
		機種名			1" F1.4 f=25mm
2015.7.30	正面図追加				
2014.12.25	更新	機種番			LM25HC
2013.4.15	作成年月日				




LM25HC

Distortion (Object)




Distortion (Object 1.0m)






Distortion (Object 0.3m)






LM25HC

MTF (Object)




MTF (Object 1.0m)






MTF (Object 0.3m)






LM25HC

F-stop: 1.4



1: Transmission vs. Wavelength Plot

Update Settings Print Window Text Annotate Zoom



TRANSMISSION VS. WAVELENGTH

MEGA2514
WED SEP 27 2006
FIELD POS: 0.0000, 0.0000 MM
FIELD IS UNPOLARIZED.

C:\ZEMAX\ MEGA2514.ZMX
CONFIGURATION 1 OF 1

