



2/3" F2/35mm C		1/2"	1/3"	
FOCAL LENGTH	f=35mm			
MAX. DIAMETER (RATIO)	F=1:2,4,8,16			
ELEMENT	4群 7枚			
PICTURE SIZE	6.6x8.8mm	4.8x6.4	3.6x4.8	
ANGLE	VER. ANGLE	10.8°	7.85°	5.89°
	HOR. ANGLE	14.4°	10.5°	7.85°
	DIA. ANGLE	17.9°	13.1°	9.81°
DISTORTION (TV)	-0.2%	-0.12%	-0.05%	
SHOOTING RANGE AT	VER.	35.8mm	26.0	19.5
MINIMUM FOCUS	HOR.	47.9mm	34.7	26.0
DISTANCE	DIA.	60.0mm	43.5	32.5
MINIMUM FOCUS DISTANCE	0.2m			
FLANGE BACK	17.526 mm in air			
BACK FOCUS	20.1mm in air (Mechanical 14.0mm in air)			
FILTER SCREW SIZE	M27.0x0.5			
FRONT/REAR EFFECTIVE DIA.	前φ21.5mm		後φ11.7mm	
MOUNT	C-MOUNT			
EXIT PUPIL	-38.7			
TEMPERATURE RANGE	-10~+50°C			
STORAGE TEMPERATURE RANGE	-20~+60°C			
RESOLUTION CENTER/CORNER	中心100本/mm		周辺 80本/mm	
WEIGHT	g			

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。



		尺度 1/1	承認 八木	製図 八木
		機種名 2/3" F2 35mm		
2014.2.24	作成年月日	LM35JCM-V		



LM35JCM-V Transmission

