


1" 0.85/35mm CS		2/3"	1/2"
FOCAL LENGTH	f=35mm		
MAX. DIAMETER (RATIO)	F=1:0.85		
PICTURE SIZE	9.6x12.8mm	6.6x8.8	4.8x6.4
ANGLE			
VER. ANGLE	16.2°	11.2°	8.1°
HOR. ANGLE	21.6°	14.9°	10.8°
DIA. ANGLE	26.8°	18.6°	13.5°
DISTORTION (TV)	-0.3%	-0.2%	-0.1%
MINIMUM FOCUS DISTANCE	3m		
FLANGE BACK	12.5 mm in air		
BACK FOCUS	22mm in air		
FILTER SCREW SIZE	M77x0.75		
FRONT/REAR EFFECTIVE DIA.	前Φ46.2mm	後Φ30mm	
MOUNT	CS-MOUNT		
EXIT PUPIL	200.8mm		
TEMPERATURE RANGE	-10~+50°C		
STORAGE TEMPERATURE RANGE	-20~+60°C		
RESOLUTION CENTER/CORNER	中心120本/mm	周辺100本/mm	
WEIGHT	9		

#### DC (DIRECT CONTROL)

DRIVE COIL	RESISTOR	190Ω (20°C)
	COLOR	RED(+) 3pin
		BLACK 4pin
BRAKE COIL	RESISTOR	1150Ω (20°C)
	COLOR	YELLOW(+) 2pin
		GREEN 1pin
DRIVE VOLT.	OPEN	LESS THAN +4V
	CLOSE	OVER THAN 0V
		W/CLOSING SPRING




**Kowa**

		尺度	1/1	承認	八木	製図	八木
		機種名	35mm F0.85 1inch				
		機種番	LM35JS5MA 外観図				


2014.3.28 作成年月日

Field Curvature

S T  
+Y

Distortion

+Y



Field Curvature / F-Tan(Theta) Distortion

LM35JS5MA

Maximum Field is 8.000 Millimeters.  
Wavelengths: 0.588

